

## 1. Product Name

- Mortar Cement

## 2. Manufacturer

Holcim (US) Inc.  
8700 Bryn Mawr Avenue  
Chicago, IL 60631  
Phone: (888) 646-5246  
E-mail: [ask@holcim.com](mailto:ask@holcim.com)  
Web: [www.holcim.us](http://www.holcim.us)

## 3. Product Description

### Usage

Mortar cement is a formulated cementitious material manufactured to be used in producing masonry mortars for use in brick, block and stone masonry units. Mortar cement mortars are recommended for above- and below-grade load bearing walls where higher bond strengths are needed. Mortar cement can also be used to produce stucco, a versatile facing material that can be applied to wall or ceiling surfaces to achieve special architectural finishes.

### Composition and Materials

Mortar cement is a combination of portland cement, plasticizers, ground limestone and air entraining additives. The above ingredients are combined and processed at Holcim (US) Inc. manufacturing facilities under controlled conditions to ensure uniform conformance.

### Types

Mortar cement is produced to meet ASTM C1329 Standard Specification for Mortar Cement and is used in preparing mortar that conforms to ASTM C270 Type N, S or M.

### Sizes

Mortar Cement is available in the following packaging sizes (bags):

- **Type N** 31.8 kilogram (70 pound)
- **Type S** 34 kilogram (75 pound)
- **Type M** 36.3 kilogram (80 pound)

### Colors

Mortar cement is gray. Holcim (US) Inc. also markets pigmented mortar products such as Holcim (US) Inc. Mortamix® Rainbow Custom Color Mortar Cements™.

### Benefits

Meets ASTM C1329 for Type N, S, or M mortar cement.



## 4. Technical Data

### Applicable Standards

- **ASTM C144** Standard Specification for Aggregate for Masonry Mortar
- **ASTM C270** Standard Specification for Mortar for Unit Masonry
- **ASTM C1329** Standard Specification for Mortar Cement

### Physical / Chemical Properties

- Mortar cement conforms to ASTM C1329 Type N, Type S or Type M mortar
- Mortar cement is used to produce ASTM C270 Type N, S or M mortar
- Requirements for sand to be used in conjunction with these products are outline in ASTM C144

## 5. Installation

### Preparatory Work

Mortar cement should be mixed in accordance with the proportions outlined in ASTM C270. Machine mixing is highly recommended. Mixing instructions are printed on each bag and shown below:

- Use 1 bag Mortar cement to 2-1/4 to 3 parts damp loose sand by volume. Sand requirements are outlined in ASTM C144.

### Batching Sequence:

- First add approximately 3/4 of the desired volume of mix water; then add 1/2 the sand followed by 1 bag of Mortar cement to the mixer.
- Finally, add the rest of the sand and remaining mix water sufficient to achieve the desired field workability.
- The combined materials should be mixed 3-5 minutes after all materials are in the mixer.

### Precautions

- Never change sand sources or mortar mixture proportion volumes during the project; undesirable color changes and performance changes to the finished product could result.
- Holcim (US) Inc. does not recommend the use of any other additives or admixtures.
- Tool all joints to the same degree of firmness in a uniform consistent manner.
- Avoid excessive re-tempering, which could result in color variations.
- Protect masonry units from weather before and after they are set in place.
- Holcim (US) Inc. does not recommend the use of acid-based cleaning solutions.
- To verify finished appearance, Holcim (US) Inc. always recommends that a job specific sample panel be erected; using the same sand, masonry units and construction practice used on your project.

### Safety Precautions

Refer to the applicable Safety Data Sheet (SDS), which should be consulted prior to the use of this product. These SDS's are available at [www.holcim.us](http://www.holcim.us).

Avoid direct contact with the skin. If contact occurs, wash skin with water as soon as possible. Exposure of sufficient duration to mortar cement can cause serious and potentially irreversible tissue destruction in the form of chemical burns. If mortar cement gets into the eyes, immediately flush eyes thoroughly with water and seek medical attention. Proper PPE is always required.

### Storage and Handling

Packaged mortar cements needing to be temporarily stored on construction sites should be stored above the ground on pallets or other means that allow airflow between the ground and the stored packaged material. Tarps or polyethylene sheeting should cover the material when not in use to prevent moisture, precipitation or high humidity from coming in contact with the bags. Prevent storage directly against walls or other structures and allow pallets to have an adequate space to allow for air circulation to reduce moisture accumulations. Construction sites and weather conditions vary and further measures may be required to protect products from moisture.

## 6. Availability and Cost

**Availability:** Mortar cement is regionally available. Contact the nearest Holcim (US) Inc. sales office for availability in your area.

**Cost:** Pricing information can be obtained from the nearest Holcim (US) Inc. sales office.

## 7. Warranty

Upon request, Holcim (US) Inc. can provide Material Certification Reports demonstrating that Mortar cement meets applicable ASTM standards. Holcim (US) Inc. will not guarantee finish work, having no control over the use of this product. Holcim (US) Inc. shall not be responsible for condition of cement after delivering to dealer or distributor.

## 8. Technical Services

Technical service is available by contacting the nearest Holcim (US) Inc. sales office at (888) 646-5246.

For questions on any technical information contained in the document, contact a Holcim (US) Inc. Technical Services Engineer for further detail.

## 9. Filing Systems

Additional product information is available from the manufacturer.

### Corporate Headquarters

Holcim (US) Inc.  
8700 Bryn Mawr Avenue  
Chicago, IL 60631  
(888) 646-5246

### Corporate Office

6211 Ann Arbor Road  
P.O. Box 122  
Dundee, MI 48131  
(888) 646-5246